This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

C08J 9/00, 3/00, E01C 13/00

(11) International Publication Number:

WO 92/19669

A1

(43) International Publication Date:

12 November 1992 (12.11.92)

(21) International Application Number:

PCT/GB92/00782

(22) International Filing Date:

28 April 1992 (28.04.92)

(30) Priority data:

9109536.4

2 May 1991 (02.05.91)

GB

(71)(72) Applicant and Inventor: BOWERS, Frank [GB/GB]; P.O. Box 1, Hoby, Melton Mowbray, Leicestershire LE14 3DT (GB).

(74) Agent: LAWRENCE, John, Gordon; McNeight & Lawrence, Regent House, Heaton Lane, Stockport SK4 1BS (GB).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, RU, SD, SE, SE (European patent), SN (OAPI patent), TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report.

(54) Title: POLYMERIC COMPOSITIONS

(57) Abstract

There is disclosed a method of producing a porous composite comprising the steps of: pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate; transporting the intermediate to site; forming a shaped mass of the intermediate; and applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT.	Austria	FI	Finland*	MI	Mali
AU	Australia	FR	France	MN	Mongolia
88	Barbados	GA	G.dvon	MIR	Mauritania
8E	Belgium	CB	United Kingdom	MW	Malawi
8F	Burkina basu	GN	Gninea	NI.	Netherlands
BG	Bulgaria	GH	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BK	Brazil	16	Ireland	RO	Romania
CA	Canada	rr	fully	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Sweiten
CII	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivaire	KR	Republic of Korea	SU	Soviet Union
Chi	Cameroin	LI	Licchtenstein	TD	Chad
CS	Czechoslovakia	l.k	Sri Lanta	TG	Togo
DE	Ciermany	L.U	Luxembourg	US	United States of America
DK.	Denousk	A1C	Manaca		

Madagascar

Spain

POLYMERIC COMPOSITIONS

This invention concerns methods and materials for the production of polymeric compositions, particularly, though by no means exclusively, suitable for use in the formation of impact absorbing surfaces or substrates to sports or play areas.

Known such impact absorbing surfaces comprise crumbs of a natural or synthetic rubber, such as EPDM for example, in a matrix of polymer, such as polyurethane for example.

The matrix may completely fill the spaces
between the crumbs to give a non-porous composition or
may simply coat the surfaces of the crumbs to cause them
to adhere leaving the interstices between the crumbs
void to give a porous product.

Either kind of composition may be laid to form a sports or play surface or to form a substrate to another surface such as that provided by synthetic turf for example.

The compositions are prepared on site immediately before use by mixing crumb, liquid polymer and if necessary a catalyst, to enable them to be laid, in the manner of asphalt, before polymerization has advanced

sufficiently to render them unworkable. Advantageously polymerization times are short to reduce the risk of damage to the finished surface before it has set.

The on site preparation and short setting time neccessitates expensive equipment and highly trained operators regardless of the size of the project.

It is an object of the present invention to provide a method and materials for production of a porous composite which overcomes the disadvantage aforesaid.

According to the present invention there is provided a method of producing a porous composite comprising the steps of :-

pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate;

transporting the intermediate to site; forming a shaped mass of the intermediate; and

applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

The shaped mass may be a horizontal layer.

The liquid polymer or pre-polymer may be in the form of an emulsion.

The liquid polymer or pre-polymer may include an inhibitor or retarder to give extended shelf life.

The liquid medium may contain a catalyst or a chemical to neutralise any inhibitor or retardant present in the liquid polymer or pre-polymer.

The liquid medium may contain a coupling agent.

The liquid medium may contain a diluent.

The particulate material may be a natural or synthetic rubber crumb.

The intermediate may be mixed with the liquid polymer or pre-polymer for a predetermined short period before formation of the shaped mass.

The mixing may be effected using a conventional cement mixer.

The liquid polymer or pre-polymer may be applied to the shaped mass by spraying or pouring.

The invention also includes compositions for use in practising the methods aforesaid.

The invention will be further apparent from the following description, which concerns, by way of example only, the laying of a running-track in accordance with one method thereof.

In general the invention comprises pre-wetting a rubber crumb with a curing agent to form a stable intermediate, at a central facility. The intermediate is bagged for storage and transport to site.

Onto a suitable sub-base a base coat comprising the intermediate is laid using conventional concrete or asphalt laying techniques and equipment.

An emulsion of polymer or pre-polymer is then sprayed over the crumb surface so as to pass through the interstices of the mix to join the crumbs into a coherent mass. Excess liquid disperses into the sub-base.

In an alternative approach the intermediate is mixed with the polymer or pre-polymer for a predetermined short time using a conventional cement mixer to initiate polymerisation before the mix is laid.

In a specific example SBR waste rubber granules having sizes in the range of 2mm - 6mm are coated with 2% by weight of a liquid medium comprising a hydraulically stable organic polyol containing the polyurethane catalyst dibutyltin mercaptide and a coupling agent (silane). The mixture is bagged for storage and use at a later date. The shelf life of the bagged mixture is greater than 12 months.

A Diphenylmethane -4, 4' Di-Isocyanate based pre-polymer having a free (-NCO) of between 8.5% and 9.5% with a viscosity of between 2800 and 3400 cp is prepared and bottled. The shelf life of pre-polymer is up to 12 months.

When required the bags of pre-wetted rubber granules and bottles of pre-polymer are transported to site.

The pre-wetted granules and pre-polymer are mixed (1 litre of pre-polymer to 40 kg of granules) by tumbling in a conventional cement mixer for between three and five minutes.

The final mixture is then laid onto a prepared sub-base and allowed to polymerise.

Polymerisation time is controlled by adjusting the amount of catalyst pre-mixed with the rubber granules.

It will be appreciated that it is not intended to limit the invention to the above example only, many variations, such as might readily occur to one skilled in the art, being possible, without departing from the scope thereof as defined by the appended claims.

Whilst the specific example is concerned with a polyurethane resin system it will be understood that other systems such as epoxy resin systems might be used.

Again, for example, the particulate material may comprise cork crumb, gravel, chipped bark or any other material suited to the intended application.

Yet again, for example, the composition may include fillers, colouring materials or other known additives.

CLAIMS

1. A method of producing a porous composite comprising the steps of :-

pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate; transporting the intermediate to site; forming a shaped mass of the intermediate; and applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

- 2. A method according to claim 1, wherein the shaped mass is a horizontal layer.
- 3. A method according to claim 1 or claim 2, wherein the liquid polymer or pre-polymer is in the form of an emulsion.
- 4. A method according to claim 3, wherein the liquid polymer or pre-polymer includes an inhibitor or retarder to give extended shelf life.
- 5. A method according to any preceding claim, wherein the liquid medium contains a catalyst or a

chemical to neutralise any inhibitor or retarder present in the liquid polymer or pre-polymer.

- 6. A method according to any preceding claim, wherein the liquid medium contains a coupling agent.
- 7. A method according to any preceding claim wherein the liquid medium contains a diluent.
- 8. A method according to any preceding claim, wherein the particulate material is a natural or synthetic rubber crumb.
- 9. A method according to any preceding claim, wherein the intermediate is mixed with the liquid polymer or pre-polymer for a predetermined short period before formation of the shaped mass.
- 10. A method according to claim 9, wherein the mixing is effected using a conventional cement mixer.
- 11. A method according to any one of claims 1-8 wherein the liquid polymer or pre-polymer is applied to the shaped mass by spraying or pouring.
- 12. A method according to any preceding claim, wherein the polymer or pre-polymer is a polyurethane based on Diphenylmethane -4, 4' Di-Isocyanate.

13. Bags of pre-wetted particles and containers of polymer or pre-polymer suitable for use in the method of any of claims 1-12.

International Application No PCT/GB 92/00782

	IEICATIO	N OF SUR	JECT MATTER (il several	classificat	tion symbols apply, indicate all) ⁶			
According	to totema	tional Pate	nt Classification (IPC) or to	poly Marie	onal Classification and IPC			
IPC5: C	08 J	9/00,	3/00, E 01 C 13	/00				
II. FIELDS	SEARCH	ED				· · · · · · · · · · · · · · · · · · ·		
			Minimum (tion Searched 7			
Classification	on System			Clas	ssification Symbols			
	!							
			1 5 01 6					
IPC5		C 08	J; E 01 C					
			Documentation Search to the Extent that such Do	ed other th	an Minimum Documentation re Included in Fields Searched ⁸			
III. DOCU	MENTS C	ONSIDER	D TO BE RELEVANT		and the coloured persons 12	Relevant to Claim No.13		
Category •					priate, of the relevant passages 12	1-2,4-5,		
Р,Х	WO, A	1, 910 ee cla	5594 (BOWERS FRA ims 1-3, 5, 10-1	ANK) 16 11	5 May 1991,	8,11		
х	US, A	, 4107	100 (JOSEF PETE	RHANS 1	ET AL)	1-5,8, 11,12		
	1	5 Augu	st 1978,	- line	64 · column	,		
	S	ee col	umn 2, line 30 40 - line 54;	cojumn	6. line 3 -	† ·		
	1 3	ine 8	abstract; claim	ms 1-5	0,	1		
	'	me o,	2000, 223,					
	1							
A	EP, A	1, 016 ee the	5895\(ALBERT FA	TIO) 2	7 December 1985,	1-13		
Ì								
į								
	1							
	1		*		·			
	1							
* Spec	zial catego	ories of ci	ted documents: 10 general state of the art whi ficular relevance	ich is not	"T" later document published after or priority date and not in con- cited to understand the princip	the international filing date lict with the application but lic or theory underlying the		
, e.	onsidered i	nent but p	ficular relevance ublished on or after the int	ernational	invention "X" document of particular relevations to considered novel or involve an inventive step			
1 (4)	IIOO GALB				involve an inventive step	oce the claimed invention		
ci	"L" document which may throw doubts on priority claim(s) or which is clied to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or integral.							
					in the arr-			
P d	ocument pater than l	ne priority	for to the international fill date claimed		-a- document wamper or the same			
IV. CER	TIFICATIO	ON Completion	of the International Search	h	Date of Mailing of this international	Search Report		
	July 1				0 4	AUG 1992		
Internati	onal Saam	hing Autho	ority		Signature of Authorized Officer			
· · · · · · · · · · · · · · · · · · ·			PATENT OFFICE		D. JARVMAN			
Form PCT	/ISA/210 (second she	et) (January 1985)					

International Application No. PCT/GB 92/00782

	International Application No. PC17GB 327		
DOCU	Relevant to Claim No		
regory .	IMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SILE Citation of Document, with indication, where appropriate, of the relevant passages		
	DE, B, 1658488 (A. KOHL & SÖHNE) 23 March 1972, see the whole document	1-13	
	23 March 1972,		
	see the whole document		
	·	1-13	
	DE, A, 2110327 (HERBERT ALLWELT) 21 September 1972, see the whole document	1.20	
	21 September 1972,		
	see the whole document		
	·		
	·		
	i e		
	·		
		·	
l			
	·		
•		•	
1			
}			
	·		
1			
1			
1		1	